



CLUTCH PARTS

CLUTCH REPLACEMENT COMPONENTS

The TRP clutch program offers a wide breadth of clutch replacement components that include clutch brakes, pilot bearings, clutch release yokes and clutch installation kits.



HINGED LOCKING CLUTCH BRAKES

The purpose of the clutch brake is to slow down or stop the transmission input shaft from rotating when the clutch pedal is depressed. Now you can replace worn or damaged clutch brakes without removing the transmission.

TRP®	Hinged Clutch Brake Application
CPBK312SP	1 ¾" (.380" thick)
CPBK313SP	2" (.380" thick)
CPBK313500SP	2" (.500" thick)
CPBK313465SP	2" (.450" thick)
CPBK313550SP	2" (.550" thick)

TORQUE LIMITING & TWO PIECE CLUTCH BRAKES

TRP®	Clutch Brake Application
CP127740	1 ¾" Torque Limiting (.380" thick)
CP127200	2" Two-Piece
CP127760	2" Torque Limiting (.380" thick)
CP127760500	2" Torque Limiting (.500" thick)
CP127760465	2" Torque Limiting (.450" thick)

PILOT BEARINGS & HIGH TEMPERATURE PILOT BEARINGS

High temperature grease is specially formulated to increase product life, exceeding the engine manufacturer's requirements. High temperature pilot bearings should be used for today's high torque engines that operate at low RPMs and higher operating temperatures.

TRP®	Pilot Bearing Application
CP6306ZZ	2.833" x 1.179"
CP6306ZZS	2.833" x 1.179" w/ snap ring
CP6305ZZ	2.440" x .985"
CP63062RS2HT	2.833" x 1.179" High Temperature
CP63062RS2SHT	2.833" x 1.179" High Temp – w/ snap ring (Mack)

CLUTCH INSTALLATION KITS

TRP®	Application
CL1771	RT Series
CL1916	RT Series w/ Mack Style Pilot Bearing
CL1910	FR Series
CL1915	FR Series w/ Mack Style Pilot Bearing



Scan the code for more information.
Get the free mobile app at <http://gettag.mobi>